




Glazing 1

PLANICLEAR 10 mm T

Last name: Alu Glass

Country: Albania

Notes: CE

LUMINOUS FACTORS

EN410 (2011-04)

Light Transmittance (TL)	89 %
Outdoor Reflectance (RLe)	8 %
Indoor Reflectance (RLi)	8 %

THERMAL TRANSMISSION

EN673-2011

Ug	5.6 W/(m².K)
Angle relative to the vertical	0 °

MANUFACTURING SIZES

Nominal Thickness	10.00 mm
Weight	25.0 kg/m²

ACOUSTICS

EN 12758

Acoustic values according to EN 12758 and from notified body

Rw (C;Ctr)	35 (-1; -2) dB
STC (ASTM E413)	N/A
OITC (ASTM E1332)	N/A

SAFETY CLASS

EN 12600

Pendulum Body Resistance	NPD
--------------------------	-----

ENERGY FACTORS

EN410 (2011-04)

Transmittance (TE)	81 %
Outdoor Reflectance (Ree)	7 %
Indoor Reflectance (Rei)	7 %
Absorptance A1 (AE1)	12 %

SOLAR FACTORS

EN410 (2011-04)

Solar Factor (g)	0.84
Shading Coefficient (SC)	0.96

COLOR RENDERING

Transmission (Ra)	98
Reflection (Ra)	98

ANTI-BURGLARY

EN 356

Burglar Resistance	NPD
--------------------	-----

CARBON FOOTPRINT

EN 15804+A2 (2019)

Global Warming Potential (GWP)	34
(kg, CO ₂ equiv/m²) European average (A1-A3)	