

LINEA CP



100%
MADE IN ITALY

Campi di applicazione:

Cartucce progettate per contrastare la formazione di calcare, proteggono tubazioni e apparecchiature dagli effetti negativi delle incrostazioni, rendendole ideali per elettrodomestici e piccoli impianti domestici.

Caratteristiche tecniche:

Temperatura massima di utilizzo: 50°C

Portata massima d'esercizio: 6.5 bar

Usi domestici: trattamento delle acque a uso domestico.

Usi industriali: impianti di osmosi.

Materiali di composizione della cartuccia

Materiale anima interna: 100% SAN alimentare

Materiali di riempimento: cristalli di polifosfato

Certificazioni: D. M. n. 174 del 06/04/2004

| DIMENSIONE | MODELLO | LUNGHEZZA | DIAMETRO INTERNO | DIAMETRO ESTERNO | MASTER-BOX | ARTICOLO |
|------------|----------|-------------|------------------|------------------|------------|----------|
| 5" | STANDARD | 126 - 129 | 28 - 29 | 71 | 60 | CP5 |
| 9" ¾ | STANDARD | 250 - 252 | 28 - 29 | 71 | 30 | CP9 |
| 10" | STANDARD | 255 - 258 | 28 - 29 | 71 | 30 | CP10 |
| 20" | STANDARD | 509 - 512 | 28 - 29 | 71 | 30 | P20 |
| 30" | STANDARD | 763 - 766 | 28 - 29 | 71 | 15 | CP30 |
| 40" | STANDARD | 1017 - 1020 | 28 - 29 | 71 | 15 | CP40 |

CP LINE



100%
MADE IN ITALY

Application fields:

Cartridges designed to prevent limescale formation, protecting pipes and equipment from the harmful effects of scaling, making them ideal for household appliances and small domestic systems.

Technical specifications:

Maximum operating temperature: 50°C

Maximum operating pressure: 6.5 bar

Domestic use: treatment of water for household applications

Industrial use: reverse osmosis system

Cartridge composition materials:

Inner core material: 100% food-grade SAN

Filling materials: polyphosphate crystals

Certificazioni: D. M. n. 174 del 06/04/2004

| DIMENSION | MODEL | LENGHT | IN DIAMETER | OUT DIAMETER | MASTER-BOX | ARTICLE |
|-----------|----------|-------------|-------------|--------------|------------|---------|
| 5" | STANDARD | 126 - 129 | 28 - 29 | 71 | 60 | CP5 |
| 9" ¾ | STANDARD | 250 - 252 | 28 - 29 | 71 | 30 | CP9 |
| 10" | STANDARD | 255 - 258 | 28 - 29 | 71 | 30 | CP10 |
| 20" | STANDARD | 509 - 512 | 28 - 29 | 71 | 30 | P20 |
| 30" | STANDARD | 763 - 766 | 28 - 29 | 71 | 15 | CP30 |
| 40" | STANDARD | 1017 - 1020 | 28 - 29 | 71 | 15 | CP40 |