

LINEA CP PRO



100%
MADE IN ITALY

Campi di applicazione:

Cartuccia anti calcare e anti corrosione a rilascio proporzionale e lunga durata

Caratteristiche tecniche:

Durata: 24 mesi

Temperatura massima di utilizzo: 50°C

Portata massima d'esercizio: 6.5 bar

Usi domestici: trattamento delle acque a uso domestico. Usi industriali: impianti di osmosi.

Materiali di composizione della cartuccia

Materiale anima interna: 100% SAN alimentare

Materiali di riempimento: cristalli di polifosfato

Certificazioni: D. M. n. 174 del 06/04/2004



DIMENSIONE	MODELLO	LUNGHEZZA	DIAMETRO INTERNO	DIAMETRO ESTERNO	MASTER-BOX	ARTICOLO
5"	STANDARD	126 - 129	28 - 29	71	60	CPPRO5
7"	STANDARD	178 - 181	28 - 29	71	74	CPPRO7
9" ¾	STANDARD	250 - 252	28 - 29	71	30	CPPRO9
10"	STANDARD	255 - 258	28 - 29	71	30	CPPRO10

CP PRO LINE



100%
MADE IN ITALY



Application fields:

Long-lasting, anti-scale and anti-corrosion cartridge with proportional release

Technical specifications:

Lifespan: 24 months

Maximum operating temperature: 50°C

Maximum operating pressure: 6.5 bar

Domestic use: treatment of water for household applications

Industrial use: reverse osmosis systems

Cartridge composition materials:

Inner core material: 100% food-grade SAN

Filling materials: polyphosphate crystals

Certification: D. M. n. 174 del 06/04/2004

DIMENSION	MODEL	LENGHT	IN DIAMETER	OUT DIAMETER	MASTER-BOX	ARTICLE
5"	STANDARD	126 - 129	28 - 29	71	60	CPPRO5
7"	STANDARD	178 - 181	28 - 29	71	74	CPPRO7
9" ¾	STANDARD	250 - 252	28 - 29	71	30	CPPRO9
10"	STANDARD	255 - 258	28 - 29	71	30	CPPRO10