


T-Mat

EROSION PROTECTION



DESCRIPTION

3-dimensional geomat with a high void ratio, made from extruded entangled synthetic monofilaments heat bonded at intersections, designed to control erosion.

APPLICATIONS

Flat green surfaces, dry slopes, reinforced soil retaining walls.

tol.

TECHNICAL DATA SHEET

Raw material		PP	
Weight	(EN 9864)	300 g/m ²	±15%
Total thickness	(EN 9863-1)	10 mm	±20%
Tensile strength MD/CMD	(EN 10319)	1,5/0,5 kN/m	-20%
Elongation at max load MD/CMD	(EN 10319)	≥50/≥50 %	

Dimensions

Roll width	2 m	±25%
Roll length	75 m	±25%
Rolls per pallet	4	

MD: Machine direction

CMD: Cross machine direction

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

The information given in this data sheet is to the best of our knowledge true and correct. TeMa srl reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

TeMa Technologies and Materials s.r.l.

Via dell'Industria, 21 - 31029 Vittorio Veneto (TV) - Tel. +39 0438 50 31 - Fax +39 0438 50 34 60
www.temacorporation.com - email: info@temacorporation.com