

T-Mix Drain 20 SS

DRAINAGE, SEPARATION, FILTRATION



DESCRIPTION

Drainage geocomposite made of a cuspated drainage core made of entangled monofilament to which two filtering geotextiles are thermally bonded.

APPLICATIONS

Foundations and below-ground building structures, flat green surfaces.

tol.

TECHNICAL DATA SHEET

Geotextile		Needle punched PP fibres	
Geotextile weight	(EN 9864)	100 g/m ²	±15%
Geocomposite thickness		20 mm	±20%
Tensile strength MD/CMD	(EN 10319)	13/13 kN/m	-20%
Elongation at max load MD/CMD	(EN 10319)	80/80 %	±25%
Drain flow capacity - Horizontal application	EN 12958 (S/R, 20kPa, i=0,04)	0,35 l/(m·s)	-20%
Drain flow capacity - Vertical application	EN 12958 (S/R, 20kPa, i=1)	2 l/(m·s)	-20%

Dimensions

Roll width	2,0 m	±3%
Roll length	20 m	±2%
Rolls/pallet	4	

S/R: Soft/Rigid

MD: Machine direction

CMD: Cross machine direction

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

The information given in this data sheet is to the best of our knowledge true and correct. TeMa srl reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

TeMa Technologies and Materials s.r.l.

Via dell'Industria, 21 - 31029 Vittorio Veneto (TV) - Tel. +39 0438 50 31 - Fax +39 0438 50 34 60

www.temacorporation.com - email: info@temacorporation.com