


No Crack

ANTI-FRACTURE



DESCRIPTION

Anti-fracture uncoupling membrane to be used under tiles, composed by a studded core in HDPE with roughened surface combined with a spunbonded polypropylene textile.

APPLICATIONS

Flooring undertile.

tol.

TECHNICAL DATA SHEET

Fabric raw material	PP
Core raw material	HDPE
Colour	Turquoise

Composite

Weight	(EN ISO 9864)	625 g/m ²	±10%
Thickness at 2 kPa	(EN ISO 9863-1)	3,5 mm	±0,5

Mechanical properties

Pull out test (cem. Glue 28 days at room temp.)	(EN 1348)	0,4 N/mm ²	±0,2
---	-----------	-----------------------	------

Roll dimensions

Length	30 m	±0,2
Width	1 m	±0,1
Roll area	30 m ²	
Rolls/pallet	12	

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

The information given in this data sheet is to the best of our knowledge true and correct. TeMa srl reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

TeMa Technologies and Materials s.r.l.

Via dell'Industria, 21 - 31029 Vittorio Veneto (TV) - Tel. +39 0438 50 31 - Fax +39 0438 50 34 60
www.temacorporation.com - email: info@temacorporation.com