

T-Bandel E



WATERPROOFING, VAPOUR BARRIER



DESCRIPTION

Three-layers waterproofing elastic band composed with an inner polyethylene core with elastic properties, bonded on both sides with PP fabric. It is used as accessory in liquid waterproofing jobs and to seal joints between Th2 Stop, Th2 Stop U and uncoupling sheets in critical points such as the connections wall to wall and wall to floor.

APPLICATIONS

Bathrooms, showers, undertile waterproofing.

tol.

TECHNICAL DATA SHEET

Fabric raw material	PP	
Core raw material	Special PP blend modified with an ethylene component	
Weight	160 g/m ²	±10%
Thickness	(EN 1849-2) 0,17 mm	±0,05


Composite

Weight	240 g/m ²	±10%
Thickness	(EN 1849-2) 0,45 mm	±0,1


Roll dimensions

Length	30 m	±0,2
Width	12,5 cm	±0,5
Rolls/box	18	


Other products and accessories:




Th2 Stop



T-Corner E



T-Corner I



T-Wall Collar

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

The information given in this data sheet is to the best of our knowledge true and correct. TeMa srl reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

TeMa Technologies and Materials s.r.l.

Via dell'Industria, 21 - 31029 Vittorio Veneto (TV) - Tel. +39 0438 50 31 - Fax +39 0438 50 34 60
www.temacorporation.com - email: info@temacorporation.com