

COMPONENTS FOR TILING MIXING VALVE SEAL

Nexiot Replast
Connection Trust

DESCRIPTION

3-layers waterproofing accessory made of PVC and polyethylene internal core bonded on both sides with a textile.


APPLICATION

Waterproofing round pipe gasket seal for shower valve and shower head.

TECHNICAL DATA SHEET

Material composition

Textile:	modified PP non-woven	
Internal core:	flexible polymer/PVC	
Colour	Light blue (other colours upon request)	
Resistance to temperature (min./max.)	-30C° / + 90C°	
Chemical resistance in the installed conditions	EN 1847 / EN 527-3	Resistant to alkali and acids



NEXI MVS mixing valve seal

DIMENSIONS

Side lenght	240 mm	±3
Hole diameter	95 mm	±1
PVC high edge	25 mm	±1
Overall membrane thickness	EN 1849-2	0,6 mm

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

Attention: due to technical reasons the colour of the material or the printing may vary slightly from batch to batch.

The above technical data represent average values. The technical information and application instructions are based on our current knowledge and expertise. However, it is the responsibility of each user to conduct trials with the original substrates in order to evaluate the suitability of our goods for the intended purpose, taking into consideration all application related parameters. If you have any further questions, please contact us.

Nexiot Replast srl

Via Nazario Sauro58/A - 42021 Barco di Bibbiano - Reggio Emilia
www.nexiot-replast.com - tecnico@nexiot-replast.com
Reg. Imprese, Cod. Fisc. e P.IVA IT02967710357 - Cap. Soc. € 20.000 - R.E.A. RE-328824 - Cod. Destinatario: XMXAUP4