

COMPONENTS FOR TILING

WALL COLLARS

DESCRIPTION

3-layers waterproofing accessories with polyethylene internal core bonded on both sides with a textile.


APPLICATION

Sealing for 3-layers waterproofing membrane junctions in critical points like pipe penetrations.

TECHNICAL DATA SHEET

Material composition

Textile:	modified PP non-woven	
Internal core:	flexible polymer	
Colour	Light blue (other colours upon request)	
Resistance to temperature (min./max.)	-30C° / + 90C°	
Chemical resistance in the installed conditions	EN 1847 / EN 527-3	Resistant to alkali and acids



WC 120-120 10 Wall Collar

DIMENSIONS

Side lenght	120 mm	±3
Internal hole diameter	15 mm	±1
External hole diameter	/	
Overall membrane thickness	EN 1849-2	0,6 mm ±0,15

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

Attention: due to technical reasons the colour of the material or the printing may vary slightly from batch to batch.

The above technical data represent average values. The technical information and application instructions are based on our current knowledge and expertise. However, it is the responsibility of each user to conduct trials with the original substrates in order to evaluate the suitability of our goods for the intended purpose, taking into consideration all application related parameters. If you have any further questions, please contact us.

Nexiot Replast srl

Via Nazario Sauro 58/A - 42021 Barco di Bibbiano - Reggio Emilia

www.nexiot-replast.com - tecnico@nexiot-replast.com

Reg. Imprese, Cod. Fisc. e P.IVA IT02967710357 - Cap. Soc. € 20.000 - R.E.A. RE-328824 - Cod. Destinatarior: XMXAUP4