

COMPONENTS FOR TILING

WALL COLLARS TPE

DESCRIPTION


3-layers waterproofing accessories with polyethylene/TPE internal core bonded on both sides with a textile.

APPLICATION

Sealing for 3-layers waterproofing membrane junctions in critical points like pipe penetrations.

TECHNICAL DATA SHEET

Material composition		
Textile:	modified PP non-woven	
Internal core:	flexible polymer/TPE	
Colour	Light blue (other colours upon request)	
Resistance to temperature (min./max.)	-30C° / + 90C°	
Chemical resistance in the installed conditions	EN 1847 / EN 527-3	Resistant to alkali and acids



WC TPE 120-120 8/50 | WC TPE 150-150 8/50 | WC TPE 150-150 19/40 | WC TPE 200-200 40/80 | Wall Collar TPE

DIMENSIONS

Side lenght	120/120 mm	150/150 mm	150/150 mm	200/200 mm	±3
Internal hole diameter	8 mm	8 mm	19 mm	40 mm	±1
External hole diameter (Back side/Front side)	60/50 mm	60/50 mm	50/40 mm	90/80 mm	±1
Flexible part	50 mm	50 mm	40 mm	80 mm	±1
Overall membrane thickness	EN 1849-2	0,6 mm	0,6 mm	0,6 mm	±0,15

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

Attention: due to technical reasons the colour of the material or the printing may vary slightly from batch to batch.

The above technical data represent average values. The technical information and application instructions are based on our current knowledge and expertise. However, it is the responsibility of each user to conduct trials with the original substrates in order to evaluate the suitability of our goods for the intended purpose, taking into consideration all application related parameters. If you have any further questions, please contact us.