

# GREEN ROOFS DRAINAGE/WATER STORAGE BOARDS

**Nexiot Replast**  
C o n n e c t i o n T r u s t

## DESCRIPTION



Double sided perforated polystyrene water storage drainage boards.

## MAIN APPLICATION

Extensive, intensive green roofs.

## TECHNICAL DATA SHEET

Material composition	HIPS (Hight Impact PolyStyrene)
Free flowing space	> 75 %
Working temperature	-30 °C to +80 °C (no tearing or crack observed)



**NEXI BOARD 40**

Water storage capacity	7,3 l/m2
Filling volume	15 l/m2
Compressive strength (EN ISO 25619-2)	170 KN/m2
Water drainage capacity (BS EN ISO 12958)	contact: S/R
20 KPa	i = 0,01
	0,974 l/m2
	i = 0,02
	1,264 l/m2
	i = 0,03
	4,733 l/m2

## DIMENSIONS

Thickness	(EN ISO 9863-1)	40 mm	±10%
Width		1000 mm	±5%
Length		2000 mm	±5%

**Storage:** cool and dry, protect against sunlight, use within 24 months after receipt.

The above technical data represent average values. The technical information and application instructions are based on our current knowledge and expertise. However, it is the responsibility of each user to conduct trials in order to evaluate the suitability of our goods for the intended purpose, taking into consideration all application related parameters. If you have any further questions, please contact us.

## Nexiot Replast srl

Via Nazario Sauro58/A - 42021 Barco di Bibbiano - Reggio Emilia  
www.nexiot-replast.com - tecnico@nexiot-replast.com  
Reg. Imprese, Cod. Fisc. e P.IVA IT02967710357 - Cap. Soc. € 20.000 - R.E.A. RE-328824 - Cod. Destinatario: XMXAUP4