

Haier Biomedical

Intelligent Protection of Life Science

-86°C ULT Freezer

DW-86L338J



Energy saving

VIP (Vacuum Insulation Panel) design with extra insulation cuts down on heat loss to cabinet by 25% and helps reduce energy consumption by more than 20% power consumption only 7.5kWh/day



Slim design

Easily fits through every standard lab door and takes a small footprint



Reliable

Cabinet temperature can reach -86°C with temp uniformity within 5°C

Complementary products



CO₂
Backup
Systems



Chart
Recorder



Stainless
Steel
Racks



Cryo
Boxes

Specifications

DW-86L338J

Technical Data

Type	-86°C ULT Freezer
Cabinet Type	Upright
Climate Class	N
Cooling Type	Direct cooling
Defrost Mode	Manual
Refrigerant	HC
Noise Level (dB)	50

Performance

Cooling performance(°C)	-86
Temperature Range(°C)	-40~-86

Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply(V/Hz)	220-240/50
Power(W)	900
Electrical Current(A)	7.5

Functions

High/Low Temperature	Y
Remote Alarm	Y
Hot Condenser	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
High Ambient Temp	Y
Door Ajar	Y



Accessories

Caster	Y
Foot	Y
Test Hole	Y/2
Shelves/Inner Doors	3/2
Temperature Recorder	Optional
USB Interface	Y
Rs232/485 Interface	Optional
CO ₂ Backup System	Optional
LN ₂ Backup System	Optional
Racks & Boxes	Optional

Dimensions

Capacity(L/Cu.Ft)	338/11.9	
Net/Gross Weight(approx)	238/278(kg)	524.7/612.9(lbs)
Interior Dimensions(W*D*H)	465*630*1165(mm)	18.3*24.8*45.9(in)
Exterior Dimensions(W*D*H)	812*893*1846(mm)	32.0*35.2*72.7(in)
Packing Dimensions(W*D*H)	875*970*2010(mm)	34.5*38.2*79.1(in)
Container load (20'/40'/40'H)	12/24/24	

Accessories & consumables

DW-86L338J

Consumables

Racks	Part Code	
Model	DCJ-54-A	DCJ-54-B (the 2 nd and the 3 rd layer)
	DCJ-44-A	DCJ-44-B (the 1 st and the 4 th layer)
Q'ty/Layer	3	
Dimension (W*D*H)	138*565*293(mm)	140*565*293(mm)
	5.4*22.2*11.5(in)	5.5*22.2*11.5(in)
	138*565*240(mm)	140*565*240(mm)
	5.4*22.2*9.4(in)	5.5*22.2*9.4(in)

Boxes	Part Code			
Model	T130	HBB-200-PP	HBB-281-PC	HBB-200-C
Material	PP	PP	PC	PC
Dimension (W*D*H)	133*133*53.5(mm) 5.2*5.2*2.1(in)			
Q'ty/Rack	20			
	16			
Total Q'ty				
Racks	6			
Boxes	120			
	96			
Vials	9720	12000	9720	12000
	7776	9600	7776	9600

Complementary products




CO2 Backup Systems



Stainless Steel Racks



Chart Recorder



Cryo Boxes

CO₂ Backup System

Model	HBX-IC
Temperature range	-40°C to -70°C

LN₂ Backup System

Model	HBX- II A
Temperature range	-90°C to -135°C

Chart Recorder

Temperature range	+50°C to -115°C
-------------------	-----------------

Others

Certificate	CE
-------------	----



Scan 2D barcode with your mobile device to learn more information about Haier Biomedical

Haier Biomedical UK

Address: 2 Birch House, Brambleside, Bellbrook Industrial Estate, Uckfield, East Sussex, TN22 1QQ, United Kingdom
 TEL: +44(0) 1825 744 696 (Head Office)
www.haierbiomedical.co.uk

Intelligent Protection
of Life Science