

HG ST PRO

PEM Hydrogen generator
with ZeroAir integrated

The HydroGen series **HG ST PRO** is able to generate up to 600 cc/min Hydrogen with purity better than 99.99999% and pressure up to 16 bar (232 PSI). An optional AirGen output can deliver hydrocarbon free pure Air with a flow up to 2000 cc/min. The HG ST PRO includes an electrolytic cell with polymeric membrane (PEM) using distilled water. The two-column PSA drying system with automatic regeneration ensures the maximum grade of hydrogen purity, and is completely maintenance-free. The HG ST PRO is the ideal Hydrogen and Air Generator for all GC-FID detectors. The on-board CPU constantly control the operating parameters to guarantee full safety. The touch-screen LCD interface provides simple and user-friendly management of all functions on the unit.

Main Applications

- Carrier gas for GC and GC-MS
- GC-FID / GC-NPD / GC-FPD
- THA
- Gas sensing

Main Advantages

- ✓ Quick installation
- ✓ Easy use
- ✓ Hydrogen flow rate up to 600 cc/min
- ✓ ZeroAir flow rate up to 2000 cc/min
- ✓ Pressure up to 16 bar (232 psi)
- ✓ Hydrogen purity: 99.99999%
- ✓ THC: < 0.1 ppm
- ✓ RS 485 and USB as standard
- ✓ LAN optional
- ✓ Dryer with no maintenance
- ✓ Reduced foot print
- ✓ High pressure GLS electronically controlled (patented)





Specifications

Models: HG ST PRO		100	160	250	350	600
General data						
	Electrolytic cell	PEM technology				
	Drying system	PSA (Pressure Swing Adsorption)				
	H2 purity	>99.99999% ¹				
	Outlet pressure	12 bars (174 psi) / 16 bars (232 psi) (optional)				
	H2 flow-rate cc/min (Max)	100	160	250	350	600
	Dimensions (WxHxD)	9.5 x 44 x 48 cm				
	Net weight (no water in tank)	18.5 kg				
Communication						
	RS485/USB	Standard				
	LAN	Optional				
Software functions						
	Parallel mode	Ready on board				
	Automatic tank refill	Standard				
Water						
	Quality	Deionized, ASTM II, <0.1uS				
	Supply pressure (min, Max)	-0.2 bars (1.4 psi), 0.5 bar (7.25 psi)				
	Internal tank capacity	0.3 l				
Electrical data						
	Type of connection	IEC 320-C13				
	Power supply voltage	100-240 Vac 50/60 Hz				
	Installed power (Max)	350W				500W
	Fuse rating (5x 20 mm)	4A 250VAC				
Connections						
	Hydrogen outlet	1/8" compression fitting				
	Water (inlet, drain)	Quick release push-in fitting				
ZeroAir section (optional)						
	Inlet pressure (Max)	8 bars (116 psi)				
	THC (Inlet Air)	100ppm				
	Outlet flow rate (max)	2000 cc/min				
	Outlet pressure (max)	Inlet pressure – 0.5 bars (8 psi) at maximum flow				
	THC (ZeroAir Outlet)	<0.1ppm				
	Inlet, Outlet ports	1/8" BSPP female				

¹ Referred to O₂ - DewPoint < -75°C

Ordering codes

Gas Generators

6920.06.010

HG ST PRO 100

6920.06.016

HG ST PRO 160

6920.06.025

HG ST PRO 250

6920.06.035

HG ST PRO 350

6920.06.060

HG ST PRO 600

Accessories (optionals)

6930.00.120

ZA 2U (Catalyst)

Consumable

6930.00.050

De-ionisation Cartridge



LNI Swissgas

www.lni-swissgas.eu

Registered office: Via Sassoferato 1, 20135 Milano MI

Logistics centre: Via E. Mattei 9, 35038 Torreglia PD