

NGA SIRIO

Ultra High purity Nitrogen and dry clean air
with long life pistons compressor integrated

NGA SIRIO produces laboratory high grade nitrogen and clean dry air for most of the laboratory applications and equipments.

Designed with safety and convenience in mind, this system generates purified nitrogen, eliminating the need for inconvenient cumbersome high-pressure gas cylinders.

The NGA SIRIO removes oxygen from air to less than 5 ppm and HC pollutants to less than 0.1ppm (if the optional scrubber is installed).

NGA SIRIO has smart low noise built-in pistons compressor, 100% oil-free.

The Ultra Pure Nitrogen is mainly used to feed ICP, ELSD, GC, FTIR and is ideal as nitrogen gas supply for all kind of Laboratory and Chromatography applications.

Main applications

- ICP / ELSD
- GC / FTIR / TOC
- Sample Evaporation
- Incubators

Main advantages

- ✓ Easy use and installation
- ✓ N₂ Purities up to 99.9995 %
- ✓ Pressure up to 5.5 bar
- ✓ N₂ flow rate up to 3 L/min + 3 L/min of dry air
- ✓ Long life and 100% oil free built-in compressor
- ✓ Reduced foot print
- ✓ Stackable with HG and ZA



Specifications



Models: NGA SIRIO	1500		3000	
N2 outlet				
Flow rate (Max)	1500 cc/min		3000 cc/min	
Outlet pressure (Max)	5.5 bar (80 psi)			
Nitrogen purity* ¹	> 99.9995%		> 99.999%	
Outlet Dew-point	<-60°C (-76°F)			
Outlet particulate	0.01 micron			
Hydrocarbon content* ²	< 0.05 ppm			
Air outlet				
Flow rate (Max)	3000 cc/min			
Outlet pressure (Max)	5.5 bar (80 psi)			
Outlet Dew-point	<-60°C (-76°F)			
Communication				
RS485	Standard			
RS232	Standard			
General data				
Supply rating	100-115 Vac 50/60Hz or 220-240Vac 50/60Hz			
Connection type	IEC320-C13			
Installation power (max)	1000W			
Fuse rating (5x20mm)	6.3A			
Net weight	<70 kg			
Dimensions (W x D x H)	430 x 700 x 630 mm			
Pneumatic connections				
Outlet port	1/8" female BSPP			
Operating/storage conditions				
Working Temperature	5-35°C (41-95°F)			
Storage Temperature	1-50°C (34-122°F)			
Humidity (max, non condensing)	70%			
Noise	< 58 dB(A)			
IP rating	IP20			
Pollution degree rating	2 (with no aromatic compounds)			
Altitude	< 2000m			

*1 The purity refers to the residual oxygen

*2 with option CH4 scrubber installed

Ordering codes

Gas Generators

6913.00.151

6913.00.301

Options

6912.01.001

Consumable

6930.01.165

NGA SIRIO 1500

NGA SIRIO 3000

CH4 scrubber for SIRIO

Outlet filter for NGA SIRIO



LNI Swissgas

www.lni-swissgas.eu

Registered office: Via Sassoferato 1, 20135 Milano MI

Logistics centre: Via E. Mattei 9, 35038 Torreglia PD