



The Öhlins kit allows lower ride-height than the height shown in the picture

Issued 31/08/2021



ROAD & TRACK

AUDI A3

PRODUCT NEWS

2020- AUDI A3

PART NO: VWS MU21 • CHASSIS CODE: 8Y



This is the latest step in the Öhlins Racing automotive philosophy – Road & Track by Öhlins.

A more than 30 year long tradition of high-end racing commitments and state-of-the-art solutions within advanced suspension technology is now available for street cars all over the world. The focus has been clear from the very beginning – superior road handling without sacrificing comfort in your day-to-day transports. The time of compromises is over.

We have also added a clever light-weight design with a majority of the parts in aluminium and on top of that all shocks have suffered through vast corrosion tests according to ISO 9227. The end result is a 2-year limited warranty on all of our products - worldwide.



#### GENERAL FEATURES

- > DFV (Dual Flow Valve)
- > Rebuildable
- > Corrosion salt spray tested (ISO 9227)
- > 2 year limited warranty
- > Springs ordered separately
- > Weight reduction compared to original suspension: -10kg

#### FRONT FEATURES

- > McPherson strut (55 mm width)
- > Single bleed adjuster
- > Height adjustable (approx. 15 mm lower than standard)
- > Coil springs (70 N/mm)
- > Use with original top mounts

#### REAR FEATURES

- > Conventional shock absorber
- > Single bleed adjuster
- > Height adjustable (approx. 15 mm lower than standard)
- > Coil springs FWD (70 N/mm), 4WD/Variant (80 N/mm)
- > Use with original top mounts

#### CANCELLATION KIT

For cars equipped OE with electronic adjustable suspension, also Öhlins cancellation kit should be used. This kit ordered separately.

| KIT               | PART NO              |             |
|-------------------|----------------------|-------------|
| 35020-15          | Cancellation kit DDC |             |
| SPRINGS           | PART NO              | SPRING RATE |
| FRONT             | 48000-19             | 70 N/mm     |
| REAR FWD          | 48010-19             | 70 N/mm     |
| REAR 4WD/ VARIANT | 48010-23             | 80 N/mm     |