



Specifiche tecniche



Model			SGT-88IV	SGT-88IV-B	SGT-88IV-W	SGT-88IV-WB
Product Description			3" Receipt Printer 58+80mm			
Effective Printing Width			72mm or 48mm			
Printing Method			Thermal Line Printing			
Resolution			203dpi			
Printing Speed			300mm/sec (Max)			
Printing Density			504dot/line or 576dot/line			
Paper Spec	Paper Width		79.5±0.5mm			
	Paper Roll Diameter		Φ80mm			
	Paper supply method		Easy paper loading			
Memory	Flash		4Mbytes			
	SDRAM		16Mbytes			
Charater	Size	Font A	12 x 24			
		Font B	9 x 24 9 x 17			
	Column Capacity	Font A	48 or 56			
		Font B	Alphanumeric Characters: 95			
	Character Set		Extended Characters: 128 x 30 Page			
			International Characters: 32			
Barcode			UPC-A,UPC-C,EAN-13,EAN-8,CODE39,ITF,CODEBAR,CODE93,CODE128, QR code			
			PC437,Katakana,PC850, PC860, PC863,PC865,WPC1252,PC866,PC852,PC858			
SDK			iOS SDK, Android SDK			
Driver			Windows CE SDK, Windows 10, Windows 7, Windows 8Windows XP/ VISTA/ 7/ 8/ 8.1/10 Linux, Android OS and Mac			
Interface			USB + COM+ LAN			
Printing command			ESC/POS/OPOS			
Environment	Temperature		Operating: 0~45℃, Stock: -10~50℃			
	Humidity		Operating: 10-80%, Stock: 10-90% (exclude paper roll)			
Dimensions			145 (W) x 215 (D) x 135 (H) mm			
Auto Cutter			2,000,000			
Weight			2.5KG			
Power	Input		AC 100V ~ 240V, 50Hz ~ 60Hz			
	Output		DC 24V, 2.5A			
Cash drawer Port control			DC 24V, 1A			
Color			Black, White, Silvery, Gold, Green			

VELOCITA: 300 mm/sec

1. Semplice ed elegante
2. Le parti importanti interne sono in materiale metallico
3. Facile caricamento della carta, con taglierina automatica, taglio completo / taglio parziale opzionale
4. Alta velocità di stampa, 300 mm/s, i materiali di consumo si cambiano velocemente, per migliorare l'efficienza del lavoro
5. Taglierina automatica, allarme carta esaurita
6. Porte COM,USB, Ethernet
7. Sensore di fine carta, sensore di quasi fine carta
8. Supporto piatto, montaggio a parete
9. Supporto piatto, montaggio a parete basso rumore, supporta la stampa di caratteri grafici e hardware ad alta velocità
10. Ampiamente usato nelle cucine dei ristoranti, nelle reception ed in altri luoghi di lavoro

MBS-SGT88IV

Stampante termica
80 mm

www.mbs-srl.com