

- 1D + 2D+ QR Code Scanner
- System Compatibility: all Windows, Linux, MacOS, Android
- Industrial IP67
- Transmission mode wired via USB cable



The actual appearance is subject to the final configuration.

## Specifications

<b>MODEL</b>	S200	
<b>Power</b>	Battery Capacity	
<b>Performance Ability</b>	System Compatibility	All Windows, Linux, MacOS, Android
	Memory Capacity	2MB (approx. 80,000 EAN barcodes)
	Scan Sensor	CMOS 1280 x 800 (1MB)
	Transmission Mode	WIRED via USB
	Scan Speed	300 scans/sec ± 2%
	Scan Precision	≥ 3 mil
	Print Contrast	≥ 20%
	Scan Depth	Code 39 (5mil): 3-9cm, Code 39 (13mil): 4-20cm, QR (15mil): 3-17cm
	Read Angle	Pitch: 40°, Roll: 360°, Skew: 40°
	Scan Angle	36° (horizontal), 27° (vertical)
	Scan Mode	Trigger, automatic induction scanning, continuous scanning
	Scan Type	1D+2D+QR code (support computer screen, mobile payment, etc.)
Decode Capability	1D: Codabar, Code 39, Interleaved 2 del 5, NEC 2 del 5, Code 93, GS1-DataBar, Code 128, GS1-128, UPC-A, UPC-E0, EAN/JAN-13, EAN/JAN-8, Code32, ecc 2D: QR code, Data Matrix, PDF417, Aztec Code	
<b>Communication Method</b>	Transmission Mode	WIRED via USB CABLE
	I/O	1 x USB
<b>Material &amp; Environment</b>	Operating Temperature	-20°C~50°C
	Storage Temperature	-20°C~60°C
	Relative Humidity	5%~95% (Non-condensing)
	IP level	IP67
<b>Regulation</b>	EMC	CE, FCC, ROHS

## Packing List

Default Items	Qty
S200 Unit	1

## Additional Images

